

# EKL 864 N R

€ 2.000



## Lievitatore con ruote Proofer with wheels



### Dotazione di serie

Imballo cartone+pallet (LxPxH mm)	845 x 740 x 1015 mm
Supporti laterali	1 dx + 1sx
Cavo	Monofase [3G 1,5]-L=1600 mm
Vaschetta raccogli condensa	

### Dimensioni

Dimensioni (LxPxH mm)	795 x 655 x 835
Peso (kg)	45,3
Passo guide (mm)	70

### Caratteristiche elettriche

Potenza elettrica (kW)	2,4
Frequenza (Hz)	50/60
Voltaggio (V)	AC 220/230
Protezione acqua	IPX4

### Caratteristiche funzionali

Alimentazione	Elettrico
Capacità	N° 8 teglie/griglie 600 x 400 mm
Vapore	/
Camera di cottura	Acciaio AISI 430
Temperatura	30 - 60 °C
Controllo temperatura	Termostato
Pannello comandi	Elettromeccanico - superiore
Temperatura preimpostata	/
Porta	2 ante apertura laterale

### Componibilità

Forno	Serie EKF 364 N- EKF 464 N - EKF 416 N
-------	--



### Equipment

Cardboard box dimensions with pallet (WxDxH mm)	845 x 740 x 1015 mm
Lateral supports	1 right + 1 left
Cable	Single-phase [3G 1,5]-L=1600 mm
Removable drip box	

### Dimensional features

Dimensions (WxDxH mm)	795 x 655 x 835
Weight (kg)	45,3
Distance between rack rails (mm)	70

### Electrical features

Power supply (kW)	2,4
Frequency (Hz)	50/60
Voltage (V)	AC 220/230
Protection against water	IPX4

### Functional features

Power	Electricity
Capacity	N° 8 trays/grids 600 x 400 mm
Steam	/
Cooking chamber	AISI 430 stainless steel
Temperature	30 - 60 °C
Temperature control	Thermostat
Control panel	Electromechanical - top side
Pre-heating temperature	/
Door	Double leaf

### Compatibility

Oven	EKF 364 N - EKF 464 N - EKF 416 N series
------	--